

## THE MUST HAVE FOR YOUR DECKING !

Want to enjoy your wooden decking? V33 UV Resistant Decking Oil is ideal for feeding and protecting your decking from water, UV rays, stains and grease. It is perfect for reviving and restoring colour to old or new decking and is also suitable for use on fences, garden sheds, gates and hot tubs etc.

### EFFICIENT

- Deeply impregnates the wood and protects thanks to its waterproofing power.
- Microporous : allows the wood to breathe.

### EASY

- Easy to apply and maintain
- Compatible with any kind of wood

## COLOURCHART

3 shades · MAT



**Clear**



**Medium oak**



**Teak**



2,5 L - 5 L





## SUPPORTS

- For most types of timber decking
- On all types of wood: European, exotic and autoclave – treated wood.



### DRYING TIME

15 min BETWEEN COATS  
24h FULLY DRY



### COVERAGE PER LITRE

+/- 4sqm<sup>2</sup> IN 2 COATS



### TOOLS

BRUSH  
ROLLER  
SPRAY GUN



TOOL  
CLEANING  
WHITE  
SPIRIT

## INSTRUCTIONS FOR USE

### PREPARATION

Ensure the surface is clean, dry and free from previous finishes and dust. Lightly sand new wood and clean old wood with V33 Tough Deck Clean and Revive.

**Important:** Oil finishes bring out the natural colour of the timber. A wet surface will be an indication of the final colour. Always test product on a spare surface or inconspicuous area for colour, compatibility and end result. Please note, this product has a milky appearance in the tin, however this disappears once dry.

### APPLICATION

*Apply the product in temperatures between 12°C and 25°C in dry weather.*

- **SOFTWOODS:** Stir well before use. Apply a generous coat of Decking Oil with a paint brush, roller or spray gun. Allow to penetrate for 15 to 30 minutes then apply the second coat without waiting for the first to dry. Continue to apply more coats of UV Resistant Decking Oil until the timber no longer absorbs the oil. Wipe off any oil that has not been absorbed into the timber with a lint-free cotton cloth and allow to dry for 24 to 48h before using the decking.

- **HARDWOODS:** Unless the hardwood is very absorbent, best results are achieved by wiping on the oil in very thin coats with a cloth. It is essential that any oil that has not been absorbed into the timber is wiped off thoroughly with a clean lint-free cloth. For new hardwoods, it is recommended to leave the wood exposed for up to 12 months before applying any finish. This allows the grain in the wood to open and breathe and aids penetration and adhesion of the finish.

Remove as much of the oil as possible from the tools after use. Do not dispose of residues and washing water/-solvents in the sink, toilet, sewer, bin,... in order to avoid discharge into the environment.

## GOOD TO KNOW

- For general maintenance clean with V33 Tough Deck Clean and Revive.
- We recommend applying 1 or 2 coats of Decking Oil at least once a year as routine maintenance. On high traffic areas re-apply 1 or 2 coats of Decking Oil as and when required.