



LONG LASTING PROTECTION

Want to enjoy your decking without a worry? V33 High Performance Decking Stain is the perfect partner for most types of exposed timber to embellish and protect it from water, UV and bad weather conditions.

HIGH PERFORMANCE

- High resistance to foot traffic, impact, UV, bad weather, stains and everyday dirt.
- Anti-slip on decking and pool areas (Tested by an independent laboratory according to the EN 16165 standard. Barefoot.)
- Protective barrier against weathering, sunlight and extreme temperatures of -10°C to +35°C.

PERFECT RESULT

- Hard wearing colours
- Matt finish wood and coloured tones to enhance the grain and preserve the natural appearance of the wood
- Easy renovation: Semi-transparent shades for direct application on stained, aged or grayed wood.

VERSATILE

- 2 in 1: Vertical and horizontal surfaces.
- Direct on all surfaces: No undercoat and no wiping.
- Compatible with any kind of wood

COLOURCHART

5 shades · 1 aspect



Clear



Light oak



Light silver



Dark silver



Gun metal



2,5 L - 5 L

SURFACES

- For all horizontal surfaces (terraces, decking), vertical surfaces (shutters, gates, shelters) and wooden furniture (chairs, tables, benches, planters, etc.)
- On all types of wood: European, exotic, composites and autoclave-treated wood.



DRYING TIME

2h BETWEEN COATS
24h FULLY DRY



COVERAGE PER LITRE

+/- 6sqm² IN 2 COATS



TOOLS

BRUSH or ROLLER



TOOL
CLEANING
WATER

INSTRUCTIONS FOR USE

PREPARATION

Ensure the surface is clean, dry and free from previous finishes and dust. Lightly sand new wood and clean old wood with V33 Tough Deck Clean and Revive.

- **HARDWOODS:** It is recommended to leave the wood exposed for up to 12 months before applying this product. This allows the grain in the wood to open and breathe and aids adhesion of the product.

APPLICATION

Apply the product in temperatures between 12°C and 25°C in dry weather.

- Stir very well before use to mix all the ingredients in the tin.
- Ensure the weather conditions are dry for 24 hours before application.
- Apply a not too thick coat of High Performance Decking Stain with a paint brush or roller. Allow to dry for 2 hours then apply a second coat.
- Any unabsorbed product remaining on the surface should be evened out with a brush to avoid unsightly marks.
- Leave to dry for at least 24 hours before use.

CAUTION: Risk of self-combustion. Wet with water any textiles or tools soiled with the product and dispose of them in a tightly closed container.

Remove as much of the oil as possible from the tools after use. Do not dispose of residues and washing water/-solvents in the sink, toilet, sewer, bin,... in order to avoid discharge into the environment.

GOOD TO KNOW

- For general maintenance clean with water.
- During the next season, we recommend to apply a further coat of High Performance Decking Stain if necessary.
- Always replace the lid otherwise the product can deteriorate.
- May not be suitable for some foreign hardwoods, test first on an inconspicuous area.