

MULTI-PURPOSE AND HIGH PROTECTION

Want to decorate your decking or give it a second life? This opaque decking paint is the ideal solution to embellish and renovate it. V33 Colour Guard Decking Paint's durability and protection of your wood is also assured with a 5-year guarantee..

HIGH PERFORMANCE

- High resistance to foot traffic, impact, UV, bad weather, stains and everyday dirt.
- Anti-slip: Class PN12 according to standard AFNOR XP P05-011 (anti slip system not suitable for pool edges).

PERFECT RESULT

- Opaque shades for direct application on stained, aged or grayed wood.
- Does not flake: Easy renovation without sanding.

VERSATILE

- 2 in 1: Vertical and horizontal surfaces.
- Direct on all surfaces: No undercoat and no wiping.
- Compatible with any kind of wood

COLOURCHART

3 shades - MAT



Light silver



Dark silver



Gunmetal



2,5 L



INSTRUCTIONS FOR USE

SURFACES

- For all horizontal surfaces (terraces, decking), vertical surfaces (shutters, gates, shelters) and wooden furniture (chairs, tables, benches, planters, etc.)
- On all types of wood: European, exotic, composites and autoclave-treated wood.



DRYING TIME

8h BETWEEN COATS
24h FULLY DRY



COVERAGE PER LITRE

+/- 5sqm² IN 2 COATS



TOOLS

BRUSH or ROLLER



TOOL
CLEANING
WATER

PREPARATION

- To ensure a perfect finish on timber previously treated with Sealer / Paint / Woodstain, please sand the existing treatment to expose the bare wood. Ensure the wood is dust-free. On exotic and hardwoods, dilute the first coat with 10% water.
- One final check: 'The Water Drop Test'. Place a small amount of water on the timber. If the water droplet absorbs into the timber, you may apply the Decking Paint. If the water droplet remains on the timber surface, the Decking Paint will not adhere. Degrease the surface with denatured alcohol.
- On new timber, wait three months before applying Decking Paint; this will then allow the timber to absorb the Decking Paint fully.
- On exotic, hardwood or oily timber : Please remove any excess oil using denatured alcohol.

APPLICATION

- *Ideal application conditions: between 12° and 25°C, in dry weather. We wouldn't recommend applying the Decking Paint in strong winds and when bad weather is forecast.*
 - Stir the paint with a mixer or wide stick, working around the bottom of the tin to mix it well, before and during use.
 - Apply the product with a brush between the grooves and edges in 2 sqm areas at a time, then paint with the roller in various directions, (top to bottom and sideways), avoiding excessive application.
 - Please allow 8 hours before applying a second coat. On highly porous or highly exposed decking, a third coat may be required.
 - Ideally, allow a further 48 hours before light usage on the decking.
- Remove as much of the paint as possible from the tools after use. Do not dispose of residues and washing water/-solvents in the sink, toilet, sewer, bin,... in order to avoid discharge into the environment.

GOOD TO KNOW

- The performance and the optimal resistance of the product is obtained after 2 weeks. Avoid stressing your surface (shocks, stains, cleaning...) during this period.
- Do not walk on the decking until 48 hours after the paint has been applied.
- To obtain the performance and resistance of this product, it is essential to apply 2 coats, without overload, even on porous substrates.
- For optimum adhesion, application must be carried out on dry wood. Wait for 3 days of dry weather before applying the 1st coat and without risk of rain within 48 hours after applying the 2nd coat.
- For exterior use only.

GUARANTEE

- 5-year guarantee when product is applied according to preparation and application instructions. On surfaces not subject to capillary rise.
- The guarantee is limited to refunding of the product (presentation of the receipt and tin required) and concerns only the appearance of the paint.